





Purpose To compare the mixing performance of the Xemex® Static Mixer with commercially available mixers.

Experimental The 2-part formulation was dispensed using Re Mixer’s automated cartridge dispenser, having preset flow rate and purge routines. After curing at room temperature for 24 hours, hardness was determined through a single-blind collection using Rex Gauge’s RX-DD Series Durometer, and in accordance with ASTM D2240.

Ashland™ Pliogrip™ 7775L

Cured Hardness



Mixing Performance The hardness data suggests that Xemex yielded good mixing performance for Ashland™ Pliogrip™ 7775L. With a retained volume of only 2.5 mL, Xemex outperformed mixers with 24 and 32 elements, which have retained volumes in the order of 5 to 15 mL. These results suggest that Xemex is a candidate to replace the current mixer in applications using Pliogrip 7775L.

Back Pressure From this data, one should expect back pressures with Xemex to be comparable to the MCH 08-24T, slightly higher than with the Ashland OEM mixer, but lower than the MCH 08-32T and MCH 06-24T at equivalent flow rates.

Formulation	Type	Mix Ratio**	Mixed** (cP)	Part A**	Part B**	Open Time** (min)	Keywords
Ashland™ Pliogrip™ 7775L	Urethane	1:1	—	14,500	20,500	5	Self-Leveling
Laboratory Technician		Cured Time		Laboratory		Report Prepared by	
Lukas Duddleston, MS		24 hours		23±2 °C 35±5 % RH		Lukas Duddleston, MS	

**As reported in Ashland’s Technical Data Sheet

THE DATA AND INFORMATION CONTAINED ON THIS REPORT IS FOR INFORMATIONAL PURPOSES ONLY. RE MIXERS, INC. HEREBY DISCLAIMS ALL REPRESENTATIONS AND WARRANTIES REGARDING THE PRODUCTS, TEST RESULTS, DATA, AND INFORMATION CONTAINED IN THIS REPORT (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE, OR INFRINGEMENT), WHETHER EXPRESS OR IMPLIED BY LAW, COURSE OF DEALING, COURSE OF PERFORMANCE, OR OTHERWISE. In addition, while the data and information contained herein is believed to be reliable, all such data and information is provided “as-is”, “with all faults”, and no warranty is expressed or implied regarding the reliability, accuracy or completeness of the data, or the results to be obtained from the use thereof. All recommendations or suggestions for use are made without guarantee and it is the user’s sole liability and responsibility to test and determine any listed product’s suitability for their own purpose and application. Ashland™ and Pliogrip™ are registered trademarks of the Ashland, Inc. Re Mixers, Inc. is not sponsored by Ashland, Inc. Any use of Ashland™, Pliogrip™, or other third party trademarks are for informational and/or comparative fair use purposes only.